```
<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions targetNamespace="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/OmniServer_dev.jws" xmlns="http:// ↙
    schemas.xmlsoap.org/wsdl/" xmlns:apachesoap="http://xml.apache.org/xml-soap" xmlns:impl="http://werewolf.cdf.utoronto↙
    .ca:8110/axis/c408h015/OmniServer_dev.jws" xmlns:intf="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/          ↙
    OmniServer_dev.jws" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:wsdl="http://schemas.xmlsoap.org/↙
    wsdl/" xmlns:wsdlsoap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <wsdl:message name="getLocksAndUIDsRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="deleteRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="startPosition" type="xsd:int"/>
    <wsdl:part name="endPosition" type="xsd:int"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="browseRequest">
  </wsdl:message>
  <wsdl:message name="browseResponse">
    <wsdl:part name="browseReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="saveDocumentResponse">
    <wsdl:part name="saveDocumentReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="getLocksRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="getLocksAndUIDsResponse">
    <wsdl:part name="getLocksAndUIDsReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="closeDocumentRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="updateLineRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="updatedLine" type="xsd:string"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="addLineRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="toAdd" type="xsd:string"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
```

```
  <wsdl:message name="getLineResponse">
    <wsdl:part name="getLineReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="unlockLineResponse">
    <wsdl:part name="unlockLineReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getDocumentRequest">
    <wsdl:part name="document" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="closeDocumentResponse">
    <wsdl:part name="closeDocumentReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="unlockLineRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="loadDocumentResponse">
    <wsdl:part name="loadDocumentReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="loadDocumentRequest">
    <wsdl:part name="documentName" type="xsd:string"/>
    <wsdl:part name="document" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="insertRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="startPosition" type="xsd:int"/>
    <wsdl:part name="endPosition" type="xsd:int"/>
    <wsdl:part name="toInsert" type="xsd:string"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getHashCodeRequest">
    <wsdl:part name="document" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="lockLineRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getLocksResponse">
    <wsdl:part name="getLocksReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="deleteResponse">
    <wsdl:part name="deleteReturn" type="xsd:long"/>
```

```
  </wsdl:message>
  <wsdl:message name="updatesRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="deleteLineResponse">
    <wsdl:part name="deleteLineReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getDocumentResponse">
    <wsdl:part name="getDocumentReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="saveDocumentRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="deleteLineRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="userID" type="xsd:long"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="insertResponse">
    <wsdl:part name="insertReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getLineRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="line" type="xsd:long"/>
    <wsdl:part name="sequenceNo" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="updatesResponse">
    <wsdl:part name="updatesReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="addLineResponse">
    <wsdl:part name="addLineReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getSequenceNoResponse">
    <wsdl:part name="getSequenceNoReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="lockLineResponse">
    <wsdl:part name="lockLineReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="updateLineResponse">
    <wsdl:part name="updateLineReturn" type="xsd:long"/>
  </wsdl:message>
  <wsdl:message name="getSequenceNoRequest">
    <wsdl:part name="documentHash" type="xsd:string"/>
    <wsdl:part name="sequenceNoOld" type="xsd:long"/>
    <wsdl:part name="lineID" type="xsd:long"/>
  </wsdl:message>
```

```
  <wsdl:message name="getHashCodeResponse">
    <wsdl:part name="getHashCodeReturn" type="xsd:string"/>
  </wsdl:message>
  <wsdl:portType name="OmniServer_dev">
    <wsdl:operation name="delete" parameterOrder="documentHash line userID startPosition endPosition sequenceNo">
      <wsdl:input message="impl:deleteRequest" name="deleteRequest"/>
      <wsdl:output message="impl:deleteResponse" name="deleteResponse"/>
    </wsdl:operation>
    <wsdl:operation name="insert" parameterOrder="documentHash line userID startPosition endPosition toInsert sequenceNo"↙
    >
      <wsdl:input message="impl:insertRequest" name="insertRequest"/>
      <wsdl:output message="impl:insertResponse" name="insertResponse"/>
    </wsdl:operation>
    <wsdl:operation name="getDocument" parameterOrder="document">
      <wsdl:input message="impl:getDocumentRequest" name="getDocumentRequest"/>
      <wsdl:output message="impl:getDocumentResponse" name="getDocumentResponse"/>
    </wsdl:operation>
    <wsdl:operation name="addLine" parameterOrder="documentHash line userID toAdd sequenceNo">
      <wsdl:input message="impl:addLineRequest" name="addLineRequest"/>
      <wsdl:output message="impl:addLineResponse" name="addLineResponse"/>
    </wsdl:operation>
    <wsdl:operation name="deleteLine" parameterOrder="documentHash line userID sequenceNo">
      <wsdl:input message="impl:deleteLineRequest" name="deleteLineRequest"/>
      <wsdl:output message="impl:deleteLineResponse" name="deleteLineResponse"/>
    </wsdl:operation>
    <wsdl:operation name="loadDocument" parameterOrder="documentName document">
      <wsdl:input message="impl:loadDocumentRequest" name="loadDocumentRequest"/>
      <wsdl:output message="impl:loadDocumentResponse" name="loadDocumentResponse"/>
    </wsdl:operation>
    <wsdl:operation name="lockLine" parameterOrder="documentHash line userID sequenceNo">
      <wsdl:input message="impl:lockLineRequest" name="lockLineRequest"/>
      <wsdl:output message="impl:lockLineResponse" name="lockLineResponse"/>
    </wsdl:operation>
    <wsdl:operation name="unlockLine" parameterOrder="documentHash line userID sequenceNo">
      <wsdl:input message="impl:unlockLineRequest" name="unlockLineRequest"/>
      <wsdl:output message="impl:unlockLineResponse" name="unlockLineResponse"/>
    </wsdl:operation>
    <wsdl:operation name="updateLine" parameterOrder="documentHash line userID updatedLine sequenceNo">
      <wsdl:input message="impl:updateLineRequest" name="updateLineRequest"/>
      <wsdl:output message="impl:updateLineResponse" name="updateLineResponse"/>
    </wsdl:operation>
    <wsdl:operation name="browse">
      <wsdl:input message="impl:browseRequest" name="browseRequest"/>
      <wsdl:output message="impl:browseResponse" name="browseResponse"/>
    </wsdl:operation>
    <wsdl:operation name="getLocks" parameterOrder="documentHash">
      <wsdl:input message="impl:getLocksRequest" name="getLocksRequest"/>
      <wsdl:output message="impl:getLocksResponse" name="getLocksResponse"/>
```

```
    </wsdl:operation>
    <wsdl:operation name="getLocksAndUIDs" parameterOrder="documentHash">
      <wsdl:input message="impl:getLocksAndUIDsRequest" name="getLocksAndUIDsRequest"/>
      <wsdl:output message="impl:getLocksAndUIDsResponse" name="getLocksAndUIDsResponse"/>
    </wsdl:operation>
    <wsdl:operation name="updates" parameterOrder="documentHash sequenceNo">
      <wsdl:input message="impl:updatesRequest" name="updatesRequest"/>
      <wsdl:output message="impl:updatesResponse" name="updatesResponse"/>
    </wsdl:operation>
    <wsdl:operation name="closeDocument" parameterOrder="documentHash">
      <wsdl:input message="impl:closeDocumentRequest" name="closeDocumentRequest"/>
      <wsdl:output message="impl:closeDocumentResponse" name="closeDocumentResponse"/>
    </wsdl:operation>
    <wsdl:operation name="getHashCode" parameterOrder="document">
      <wsdl:input message="impl:getHashCodeRequest" name="getHashCodeRequest"/>
      <wsdl:output message="impl:getHashCodeResponse" name="getHashCodeResponse"/>
    </wsdl:operation>
    <wsdl:operation name="getLine" parameterOrder="documentHash line sequenceNo">
      <wsdl:input message="impl:getLineRequest" name="getLineRequest"/>
      <wsdl:output message="impl:getLineResponse" name="getLineResponse"/>
    </wsdl:operation>
    <wsdl:operation name="getSequenceNo" parameterOrder="documentHash sequenceNoOld lineID">
      <wsdl:input message="impl:getSequenceNoRequest" name="getSequenceNoRequest"/>
      <wsdl:output message="impl:getSequenceNoResponse" name="getSequenceNoResponse"/>
    </wsdl:operation>
    <wsdl:operation name="saveDocument" parameterOrder="documentHash">
      <wsdl:input message="impl:saveDocumentRequest" name="saveDocumentRequest"/>
      <wsdl:output message="impl:saveDocumentResponse" name="saveDocumentResponse"/>
    </wsdl:operation>
  </wsdl:portType>
  <wsdl:binding name="OmniServer_devSoapBinding" type="impl:OmniServer_dev">
    <wsdlsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="delete">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="deleteRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="deleteResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="insert">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="insertRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
```

```
      </wsdl:input>
      <wsdl:output name="insertResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="getDocument">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="getDocumentRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="getDocumentResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="addLine">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="addLineRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="addLineResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="deleteLine">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="deleteLineRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="deleteLineResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="loadDocument">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="loadDocumentRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="loadDocumentResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
```

```
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="lockLine">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="lockLineRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="lockLineResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="unlockLine">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="unlockLineRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="unlockLineResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="updateLine">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="updateLineRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="updateLineResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="browse">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="browseRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="browseResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="getLocks">
      <wsdlsoap:operation soapAction=""/>
```

```
      <wsdl:input name="getLocksRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="getLocksResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="getLocksAndUIDs">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="getLocksAndUIDsRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="getLocksAndUIDsResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="updates">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="updatesRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="updatesResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="closeDocument">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="closeDocumentRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="closeDocumentResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="getHashCode">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="getHashCodeRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use="encoded"/>
      </wsdl:input>
```

```
      <wsdl:output name="getHashCodeResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="getLine">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="getLineRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="getLineResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="getSequenceNo">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="getSequenceNoRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="getSequenceNoResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="saveDocument">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="saveDocumentRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://DefaultNamespace" use=↙
    "encoded"/>
      </wsdl:input>
      <wsdl:output name="saveDocumentResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/" namespace="http://werewolf.cdf.utoronto.↙
    ca:8110/axis/c408h015/OmniServer_dev.jws" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
  </wsdl:binding>
  <wsdl:service name="OmniServer_devService">
    <wsdl:port binding="impl:OmniServer_devSoapBinding" name="OmniServer_dev">
      <wsdlsoap:address location="http://werewolf.cdf.utoronto.ca:8110/axis/c408h015/OmniServer_dev.jws"/>
    </wsdl:port>
  </wsdl:service>
</wsdl:definitions>
```